Lot 1368 The Point at Lake Norman Fast Track Septic System Information

Number of Bedrooms	4
Basement or Crawl	Crawl Space
Design Flow (gpd)	480
LTAR (gpd/ft2)	0.3
Primary System Type	**LP PPBPS**
No. Lines	3 (See Table)
Total Linear Feet	300
Trench Width	2' min.
Trench Spacing	8' min.
Pump Required	Yes
Distribution Device	Gate Valve Box w/ LPP Distribution
Maintenance Agreement Required	Yes
Length and Diameter of Supply Pipe	105' of 2" SCH 40 PVC
Size of laterals	1 1/4" SCH 40 PVC
Flow Rate through the system	34.5 gpm
Elevation head	Approx. 6'
Pressure head	3.0'
Friction head	2.3'
20% Contingency	2.25
Total Head	13.55
Pump Requirements	34.5 gpm @ 13.6' of head; use Goulds WE03M pump or equivelent with compatible electrical
Dosing Volume	248 gal -1.9 doses/day @ design flow*
Volume of water pumped per dose	Calculated to specific tank by measure or dealer engineering specifications (1 cubic ft. of water equals 7.48 gal.)
Pump Run per dose	approx. 7.2 min.
Check Valve	No
Siphon Break hole	Yes
Repair System	**LP PPBPS**
Total Linear Feet	334


***Before placement of cap block, one panel on each line near the center of the field should be observed filling to make certain that it does not overflow top chamber into air chambers of panel. If overflow occurs, reduce floats by 25 gallons and reset until no overflow is observed.**

Table 1: Summary of Primary and Repair Nitrification Line Specifications

Line No.	Use	Line Color	System Type	Line Length (Ft.)	Rod Reading Elev. (Ft.)	Panels	Holes	Hole Spacing	Hole Size (In.)
1	Repair	Pink	LPPPBPS	27'	3.78'				
2	Repair	Orange	LPPPBPS	50'					
3	Repair	White	LPPPBPS	61'					
4	System	Red	LPPPBPS	100' centerfed		23	23	1 per panel	5/32"
5	System	Pink	LPPPBPS	100' centerfed		23	23	1 per panel	5/32"
6	Repair	Orange	LPPPBPS	25'					
7	System	Blue	LPPPBPS	100' centerfed		23	23	1 per panel	5/32"
8	Repair	White	LPPPBPS	73'					
9	Repair	Orange	LPPPBPS	62'					
10	Repair	Pink	LPPPBPS	36'	10.7'	Total: 69	Total: 69 (1 in each panel turned up)		
				Total System: 300'					
				Total Repair: 334'					

Tank	~~White~~ Red	1500 gal (2 compartment)	2.5'
Pump Tank	~~White~~	1500 gal.	2.5'
House	Blue	Left Rear Corner	2.6

GOULDS PUMPS



Submersible Effluent Pump

MODEL 3885

WE Series

PROSURANCE AVAILABLE FOR RESIDENTIAL APPLICATIONS.

APPLICATIONS

Specifically designed for the following uses:

- Homes
- Farms
- Trailer courts
- Motels
- Schools
- Hospitals
- Industry
- Effluent systems

SPECIFICATIONS

Pump

- Solids handling capabilities: ¾" maximum.
- Discharge size: 2" NPT.
- Capacities: up to 140 GPM.
- Total heads: up to 128 feet TDH.
- Temperature: 104°F (40°C) continuous 140°F (60°C) intermittent.
- See order numbers on reverse side for specific HP, voltage, phase and RPM's available.

FEATURES

■ **Impeller:** Cast iron, semi-open, non-clog with pump-out vanes for mechanical seal protection. Balanced for smooth operation. Silicon bronze impeller available as an option.

■ **Casing:** Cast iron volute type for maximum efficiency. 2" NPT discharge.

■ **Mechanical Seal:** SILICON CARBIDE VS. SILICON CARBIDE sealing faces. Stainless steel metal parts, BUNA-N elastomers.

■ **Shaft:** Corrosion-resistant, stainless steel. Threaded design. Locknut on all models to guard against component damage on accidental reverse rotation.

■ **Fasteners:** 300 series stainless steel.

■ Capable of running dry without damage to components.

■ Designed for continuous operation when fully submerged.

MOTORS

■ Fully submerged in high-grade turbine oil for lubrication and efficient heat transfer.

■ Class B insulation on ⅓-1½ HP models.
■ Class F insulation on 2 HP models.

Single phase (60 Hz):

- Capacitor start motors for maximum starting torque.
- Built-in overload with automatic reset.
- SJTOW or STOW severe duty oil and water resistant power cords.
- ⅓ and ½ HP models have NEMA three prong grounding plugs.
- ¾ HP and larger units have bare lead cord ends.

Three phase (60 Hz):

- Class 10 overload protection must be provided in separately ordered starter unit.
- STOW power cords all have bare lead cord ends.

■ **Designed for Continuous Operation:** Pump ratings are within the motor manufacturer's recommended working limits, can be operated continuously without damage when fully submerged.

■ **Bearings:** Upper and lower heavy duty ball bearing construction.


■ **Power Cable:** Severe duty rated, oil and water resistant. Epoxy seal on motor end provides secondary moisture barrier in case of outer jacket damage and to prevent oil wicking. Standard cord is 20'. Optional lengths are available.

■ **O-ring:** Assures positive sealing against contaminants and oil leakage.

AGENCY LISTINGS

C SP US — Tested to UL 778 and CSA 22.2 108 Standards By Canadian Standards Association File #LR38540

Goulds Pumps is ISO 9001 Registered.



Goulds Pumps

ITT Industries

© 2003 Goulds Pumps
Effective July, 2003
B3885