# LEGEND

*use the following standard abbreviations*

| DSCAPE POSITION | GROUP | SOIL TEXTURE | CONVENTIONAL 1955 LTAR | LPP 1957 LTAR | MINERALOGY/ CONSISTENCE | STRUCTURE |
|---|---|---|---|---|---|---|
| Concave Slope) | I | S (Sand) | 1.2 - 0.8 | 0.6 - 0.4 | NEXP (Non-expansive) | G (Single Grain) |
| Convex Slope) | | LS (Loamy Sand) | | | SEXP (Slightly Expansive) | M (Massive) |
| Drainage Way) | | | | | EXP (Expansive) | CR (Crumb) |
| Debris Slump) | II | SL (Sandy Loam) | 0.8 - 0.6 | 0.4 - 0.3 | | GR (Granular) |
| Flood Plain) | | L (Loam) | | | | SBK (Subangular Block |
| Foot Slope) | | | | | | ABK (Angular Blocky) |
| Head Slope) | III | SI (Silt) | 0.6 - 0.3 | 0.3 - 0.15 | | PL (Platy) |
| Linear Slope) | | SICL (Silty Clay Loam) | | | | PR (Prismatic) |
| Nose Slope) | | CL (Clay Loam) | | | | |
| Ridge) | | SCL (Sandy Clay Loam) | | | MOIST | WET |
| Boulder Slope) | | SLC (Silt Loam Clay) | | | | |
| Terrace) | IV | SC (Sandy Clay) | 0.4 - 0.1 | 0.2 - 0.05 | VFR (Very Friable) | NS (Non-sticky) |
| | | SIC (Silty Clay) | | | FR (Friable) | SS (Slightly Sticky) |
| | | | | | FI (Firm) | S (Sticky) |
| | | O (Organic) | None | | VFI (Very Firm - Very Sticky) | VS (Very Sticky) |
| | | | | | EFI (Extremely Firm) | NP (Non-plastic) |
| | | | | | | SP (Slightly Plastic) |
| | | | | | | P (Plastic) |
| | | | | | | VP (Very Plastic) |

ES

| | |
|---|---|
| *IZON DEPTH* | In inches below natural soil surface |
| *TH OF FILL* | In inches from land surface |
| *RUCTIVE HORIZON* | Thickness and depth from land surface |
| *OLITE* | S(suitable) or U(unsuitable) |
| *VETNESS* | Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color and designation |
| *SIFICATION* | S (Suitable), PS (Provisionally Suitable), or U (Unsuitable) |

ation of saprolite shall be by pits.

-erm Acceptance Rate (LTAR): gal/day/ft²

**Show profile locations and other site features (dimensions, reference or benchmark, and North).**

