
(6:10)



FLOOR PLAN 1/4" = 1'-0"

TOTAL LIVING ——— 2388 sq. ft.
GARAGE & STORAGE ——— 540 sq. ft.
BONUS ROOM ——— 343 sq. ft.

PLAN NOTES:

1. VERIFY ALL LOCAL CODES, ENERGY TYPES, AND SITE CONDITIONS PRIOR TO CONSTRUCTION. THE OWNER AND BUILDER SHALL BE SOLELY RESPONSIBLE FOR CODE COMPLIANCE.
2. REVIEW SELECTED MECHANICAL SYSTEMS WITH OWNER PRIOR TO CONSTRUCTION.

   REVIEW SUB-CONTRACTORS LOCATIONS OF THE WATER HEATER AND HVAC UNIT(S) WITH THE OWNER PRIOR TO CONSTRUCTION. ENSURE COMPLIANCE WITH LOCAL BUILDING CODE REQUIREMENTS AND MANUFACTURER REQUIREMENTS.

   H.V.A.C. EQUIPMENT IN THE ATTIC SPACE SHALL BE ACCESSIBLE BY AN OPENING LARGER THAN THE LARGEST PIECE OF EQUIPMENT (TO ALLOW REMOVAL OF THE EQUIPMENT) AND IN NO CASE LESS THAN 22"x36".
3. SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION.
4. INSULATE AROUND ALL BATHS AND UTILITY ROOM.
5. TYPICAL WALL, 2x4'S @ 16" O.C. UNLESS OTHERWISE DIMENSIONED.
6. PROVIDE SMOKE DETECTORS AS REQUIRED BY CODE.
7. PROVIDE DOORBELLS, TRANSFORMER, AND CHIME.

DOOR SCHEDULE

SYMBOL ○

MARK	SIZE	QUAN.	DESCRIPTION
1	3'-0" x 6'-8"	1	EXT., THREE-QUARTER GLASS W/ 16" SIDELITE & ARCH HEAD TRANSOM #
2	2'-8" x 6'-8"	1	EXT., FULL GLASS W/ 12" TRANSOM #
3	(2) 2'-6" x 6'-8"	2	EXT., FULL GLASS W/ 12" TRANSOM #
4	2'-0" x 6'-8"	1	EXT., 1 HOUR FIRE-RATED
5	16'-0" x 7'-0"	1	GARAGE
6	2'-0" x 6'-8"	6	INT.
7	2'-4" x 6'-8"	5	INT.
8	2'-0" x 6'-8"	3	INT.
9	(2) 2'-0" x 6'-8"	1	INT.
10	(2) 2'-6" x 6'-8"	2	INT. BIFOLD
11	3'-0" x 6'-8"	1	EXT. SCREEN

SEE ELEVATION FOR TRANSOM.

ELECTRICAL LEGEND


SYMBOL	DESCRIPTION
⊖	DUPLEX OUTLET (GROUNDED TYPE)
WP⊖	WEATHER PROOF DUPLEX OUTLET
⊖	ABOVE COUNTER LOCATION
⊖	FLUSH FLOOR DUPLEX OUTLET, OWNER VERIFY LOCATION
◉	220 VOLT OUTLET OR CONNECTION
⊹	CEILING MOUNTED LIGHT FIXTURE
⊹	WALL BRACKET MOUNTED LIGHT FIXTURE
⊹	SUSPENDED CEILING MOUNTED LIGHT FIXTURE
◧	RECESSED DIRECTIONAL CEILING LIGHT FIXTURE
□	RECESSED CEILING LIGHT FIXTURE
□	RECESSED LIGHT FOR WET AREA
▭	UNDER CABINET FLUORESCENT LIGHT
⊠	EXTERIOR CAST ALUMINUM FLOOD LIGHTS
✳	CEILING MOUNTED PADDLE FAN w/ LIGHT
⊘	CEILING MOUNTED FAN - EXHAUST
⊛	CEILING MOUNTED FAN AND HEATER
⊛	CEILING MOUNTED FAN, LIGHT, AND HEATER

WINDOW SCHEDULE

SYMBOL □

MARK	SIZE	QUAN.	DESCRIPTION
A	2'-8" x 6'-2"	5	D.H.
B	(2) 2'-8" x 6'-2"	1	D.H.
C	(2) 2'-8" x 5'-6"	3	D.H.
D	2'-8" x 5'-10"	2	D.H.
E	(2) 2'-8" x 5'-10"	1	D.H., 6" ARCH HEAD TRANSOM
F	(2) 2'-4" x 6'-6"	1	D.H.
G	3'-0" x 4'-2"	1	D.H.
H	(2) 2'-0" x 5'-2"	1	D.H.
J	1'-8" x 3'-2"	2	FIXED, ARCH HEAD #
K	2'-8" x 5'-6"	1	D.H.
L	(2) 2'-8" x 6'-2"	1	D.H. W/ HALF CIRCLE TRANSOM #

ALL WINDOWS ARE INSULATED AND WEATHERSTRIPPED.
VERIFY LOCAL CODE EGRESS WINDOW REQUIREMENTS PRIOR TO CONSTRUCTION.
WINDOW MANUFACTURER TO PROVIDE TEMPERED GLASS WHERE REQUIRED BY CODE.
VERIFY WINDOW MODEL NUMBERS AND SIZES WITH MANUFACTURER BEFORE STARTING CONSTRUCTION.
SEE ELEVATION.



BONUS ROOM FLOOR PLAN 1/4" = 1'-0"

Acknowledgement Of
Plans Submittal ONLY!
Marcus Lebo Date 7/3/13
Barry Mozely Date 7/3/13

Copyrighted © Donald A. Gardner Architects, Inc. and/or Donald A. Gardner, Inc.

REG # 748584

It's a violation of the Federal Copyright Act to copy these plans. The federal copyright statute provides for monetary damages for each infringement of copyright from $250 up to $150,000.

Permission to construct the building depicted in the drawings is expressly conditioned on the full and timely payment of all fees otherwise due Donald A. Gardner Architects, Inc. and/or Donald A. Gardner, Inc. These plans can be used to construct ONE house only and the license CANNOT be transferred. See additional drawing notes on the packaging.

This copyright notice & copyright management information under the Digital Millennium Copyright Act, and Donald A. Gardner Architects Inc. and/or Donald A. Gardner, Inc. requires its inclusion on all copies to discourage and police copyright infringement. Unauthorized reproduction or usage of these documents or removal of the notification is subject to prosecution.

DO NOT SCALE DRAWINGS.


COPYRIGHT @ 01/12/08 ALL RIGHTS RESERVED BY DONALD A. GARDNER, INC.
NOT TO BE COPIED OR REPRODUCED WITHOUT WRITTEN PERMISSION

ALL FEDERAL, STATE, AND LOCAL CODES, ORDINANCES, REGULATIONS AND MANUFACTURER'S INSTRUCTIONS ETC. SHALL BE CONSIDERED AS PART OF THE SPECIFICATIONS FOR THIS BUILDING AND SHALL TAKE PRECEDENCE OVER ANYTHING SHOWN, DESCRIBED, OR IMPLIED WHERE SAME ARE AT VARIANCE. THESE PLANS ARE NOT DRAWN FOR ANY PARTICULAR LOCALE. YOU ARE RESPONSIBLE FOR DETERMINING AND ENSURING COMPLIANCE WITH ALL APPLICABLE CODES AND MANUFACTURER'S REQUIREMENTS.

△ 11/8/06

DONALD A. GARDNER, INC.®
ARCHITECTS • PLANNERS®
P.O. BOX 26178 • GREENVILLE S.C. • 29616
864 • 288 • 7580
www.dongardner.com/BP

DESIGN NO. 1154
SHEET OF 3 7
OR WSK
FLOOR PLAN



FOUNDATION AND FLOOR FRAMING PLAN

1/4" = 1'-0"

NOTE: IN LIEU OF INSTALLING 6 MIL POLYETHYLENE MOISTURE BARRIER IN CRAWL SPACE, CONTRACTOR MAY PROVIDE A TOTAL OF (3) 16"x8" FOUNDATION VENTS (ASSUMED 50% NET FREE AREA PER VENT)

Acknowledgement Of Plans Submittal ONLY!

_____ Date _____

_____ Date _____

Copyrighted © Donald A. Gardner Architects, Inc. and/or Donald A. Gardner, Inc.

REG #_____

It's a violation of the Federal Copyright Act to copy these plans. The federal copyright statute provides for monetary damages for each infringement of copyright from $200 to $150,000.

Permission to construct the residence pictured in the drawings is expressly conditioned on the full and timely payment of all fees otherwise due Donald A. Gardner Architects, Inc. and/or Donald A. Gardner, Inc. These plans can be used to construct ONE house only and the license CANNOT be transferred. See additional licensing terms on the packaging.

This copyright notice is "copyright management information" under the Digital Millennium Copyright Act, and Donald A. Gardner Architects, Inc. and/or Donald A. Gardner, Inc. reserves its inclusion on all copies to discourage and police copyright infringement. Unauthorized reproduction or usage of these documents or removal of the notification is subject to prosecution.

GENERAL NOTES

A. GENERAL:

1. AT THE TIME OF CREATION, PLANS CONFORM TO "CABO ONE AND TWO FAMILY DWELLING CODES" OR THE "INTERNATIONAL RESIDENTIAL CODES" HOWEVER MODIFICATIONS MAY BE NECESSARY TO COMPLY WITH LOCAL AND STATE CODES.
2. CONTRACTOR SHALL VERIFY ALL DIMENSIONS.
3. CONTRACTOR SHALL COMPLY WITH THE CONTENTS OF THE SPECIFICATIONS FOR THIS HOUSE.
4. ALL WOOD USED IN CONSTRUCTION OF DECKS AND STEPS SHALL BE TREATED. FASTENERS FOR TREATED WOOD (NAILS, BOLTS, HARDWARE, ETC.) SHALL BE GALVANIZED.
5. CONTRACTOR SHALL INSTALL GROUND FAULT INTERRUPT OUTLETS AS PER CODE.
6. INSTALL ROOFING MATERIALS ACCORDING TO MANUFACTURERS RECOMMENDATIONS FOR THE AREA AND CLIMATE, INCLUDING BUT NOT LIMITED TO SHINGLES, TILES, FELTS, FLASHING, AND FASTENING DEVICES
7. HEARTH DIMENSIONS DETERMINED BY CODE
8. INSTALL ALL EXTERIOR FINISH MATERIALS PER MANUFACTURER'S RECOMMENDATIONS (I.E. CONTROL JOINTS, ATTACHMENT/ ANCHORING DEVICES, FLASHING, SEALANTS, ETC.)

B. FRAMING:

1. JOIST SPANS WERE DETERMINED ON THE BASIS OF THE ALLOWABLE STRESSES IN THE "1991" GRADING RULES OF THE SOUTHERN PINE INSPECTION BUREAU" GRADE NUMBER TWO (2) KILN DRIED.
2. PROVIDE DOUBLE JOISTS BELOW ALL PARALLEL PARTITIONS, ABOVE AND AROUND ALL OPENINGS NOT INDICATED ON DRAWINGS.
3. PROVIDE SOLID BLOCKING BETWEEN FLOOR JOISTS UNDER WALLS THAT ARE PERPENDICULAR TO FLOOR JOISTS
4. SHEATH ALL EXTERIOR WALLS WITH NOMINAL 1/2" STRUCTURAL GRADE 2 PLYWOOD OR NOMINAL 1/2" OSB (ORIENTED STRAND BOARD).

C. VENTILATION:

1. PROVIDE CONTINUOUS RIDGE VENTS ON ALL ROOFS. LOCATE DOUBLE RIDGE BEAMS TO ALLOW FOR PROPER INSTALLATION OF RIDGE VENTS.
2. PROVIDE CONTINUOUS EAVE TO WALL VENTS AT ALL JUNCTURES OF SLOPED ROOFS AND VERTICAL WALLS

D. FOOTINGS:

1. CARRY ALL FOOTINGS TO FIRM UNDISTURBED BEARING:
   A. 16" x 12" FOOTING FOR 8" OR 9" FOUNDATION WALL WITH (2) #4 REINF. RODS CONTINUOUS
   B. 24" x 12" FOOTING FOR 12" FOUNDATION WALL WITH (2) #4 REINF. RODS CONTINUOUS.

E. PIER FOOTINGS:


PIER FOOTINGS (TYPICAL UNLESS NOTED OTHERWISE)


1. PROVIDE 1'-8"x2'-4"x1'-8" DEEP CONCRETE FOOTING WITH (3) #4 REINF. RODS EACH WAY UNDER 8"x16" MASONRY PIERS.
2. PROVIDE 2'-4" SQUARE x 1'-8" DEEP CONCRETE FOOTING WITH (3) #4 REINF. RODS EACH WAY UNDER 16" SQUARE MASONRY PIERS.
3. PROVIDE 2'-8"x2'-8"x1'-8" DEEP CONCRETE FOOTING WITH (3) #4 REINF. RODS EACH WAY UNDER 20" SQUARE MASONRY PIERS.
4. PROVIDE 2'-0"x2'-4"x1'-8" DEEP CONCRETE FOOTING WITH (3) #4 REINF. RODS EACH WAY UNDER 8"x16" MASONRY PIERS.
5. PROVIDE 2'-0"x2'-8"x1'-8" DEEP CONCRETE FOOTING WITH (3) #4 REINF. RODS EACH WAY UNDER 12"x20" MASONRY PIERS.
6. FILL PIERS SOLID WITH 2500 P.S.I. CONCRETE, TYPICAL.
7. HEIGHT OF PIERS:
   A. PIERS LESS THAN 36" IN HEIGHT MAY BE 8"x16" OR AS NOTED ON FOUNDATION PLAN.
   B. PIERS BETWEEN 36" AND 80" IN HEIGHT SHALL BE A MINIMUM OF 16"x16".
   C. PIERS GREATER THAN 80" IN HEIGHT SHALL BE A MINIMUM OF 16"x16" WITH (4) CONTINUOUS #5 BARS.

F. CHIMNEY CONSTRUCTION:

1. USE NOMINAL 1/2" STRUCTURAL GRADE 2 PLYWOOD OR NOMINAL 1/2" OSB (ORIENTED STRAND BOARD) SHEATHING.
2. SPLICE ONLY ONE CORNER STUD AT ANY SPLICE. STAGGER SPLICES AT LEAST 3'-0" AND USE (4) STUDS PER CORNER.
3. USE 10d NAILS @ 4" O.C. AROUND ALL PLYWOOD EDGES AND 12" O.C. AT ALL INTERMEDIATE SUPPORTS.
4. PROVIDE BLOCKING BETWEEN STUDS AT 4'-0" INTERVALS.
5. CONTRACTOR TO VERIFY CHIMNEY FINISH MATERIAL WITH OWNER PRIOR TO CONSTRUCTION. IF BRICK MASONRY IS REQUIRED, CONTRACTOR TO MODIFY CONSTRUCTION OF FIREPLACE AND CHIMNEY AS REQUIRED.

FOUNDATION LEGEND






1/2 SECTION

3/4" = 1'-0"

SEE OTHER WALL SECTIONS FOR ADDITIONAL INFORMATION



TYPICAL PIPE THRU FLOOR

3/4" = 1'-0"

DO NOT SCALE DRAWINGS.

COPYRIGHT @ 01/12/06 ALL RIGHTS RESERVED BY DONALD A. GARDNER, INC. NOT TO BE COPIED OR REPRODUCED WITHOUT WRITTEN PERMISSION

ALL FEDERAL, STATE, AND LOCAL CODES, ORDINANCES, REGULATIONS AND MANUFACTURER'S INSTRUCTIONS ETC. SHALL BE CONSIDERED AS PART OF THE SPECIFICATIONS FOR THIS BUILDING AND SHALL TAKE PRECEDENCE OVER ANYTHING SHOWN, DESCRIBED, OR IMPLIED WHERE SAME ARE AT VARIANCE. THESE PLANS ARE NOT DRAWN FOR ANY PARTICULAR LOCALE. YOU ARE RESPONSIBLE FOR DETERMINING AND ENSURING COMPLIANCE WITH ALL APPLICABLE CODES AND MANUFACTURERS REQUIREMENTS.

DONALD A. GARDNER, INC.®
ARCHITECTS • PLANNERS®
P.O. BOX 26178 • GREENVILLE S.C. • 29616
864 • 288 • 7580
www.dongardner.com/BP

DESIGN NO. 1154

SHEET OF 2 7 DR. WBK

FOUNDATION PLAN