...OF ENVIRONMENTAL HEALTH:
...-SITE WASTEWATER SECTION

PROPERTY ID #:
COUNTY:

SOIL/SITE EVALUATION
for ON-SITE WASTEWATER SYSTEM

...ER: Mike Sullivan
...DRESS: APPLICANT:
...OPOSED FACILITY: APPLICATION DATE: DATE EVALUATED: 7/11/...
...CATION OF SITE: Lot 26 Crystal Bay PROPOSED DESIGN FLOW (.1949): PROPERTY SIZE:
...ATER SUPPLY: ☐ Private ☐ Public ☐ Well ☐ Spring ☐ Other PROPERTY RECORDED:
...ALUATION METHOD: ☐ Auger Boring ☐ Pit ☐ Cut
...PE OF WASTEWATER: ☐ Sewage ☐ Industrial Process ☐ Mixed

.1940 LAND-SCAPE POSITION/ SLOPE %	HORI-ZON DEPTH (IN.)	SOIL MORPHOLOGY (.1941) .1941 STRUCTURE/ TEXTURE	.1941 CONSISTENCE/ MINERALOGY	OTHER PROFILE FACTORS .1942 SOIL WETNESS/ COLOR	.1943 SOIL DEPTH	.1956 SAPRO CLASS	.1944 RESTR HORIZ	PROFILE CLASS & LTAR
	0-10"	Brn to Rd/Brn SCL						
	10"-42"	Rd/Brn C/Cl m-w	SBK SS SP SFR				w/ Common	PS
		Mica Flakes & Fe	to many			SAP	Indus	
	42-48"	LSAP w/ C/Cl Indus						1.3 to 42"

DESCRIPTION	INITIAL SYSTEM	REPAIR SYSTEM
ble Space (.1945)		
Type(s)		
AR		

OTHER FACTORS (.1946):
SITE CLASSIFICATION (.1948):
EVALUATED BY:
OTHER(S) PRESENT:

use the following standard abbreviations.

GROUP	SOIL TEXTURE	CONVENTIONAL .1955 LTAR	LPP .1957 LTAR	MINERALOGY/ CONSISTENCE	STRUCTURE
I	S (Sand) LS (Loamy Sand)	1.2 - 0.8	0.6 - 0.4	NEXP (Non-expansive) SEXP (Slightly Expansive) EXP (Expansive)	G (Single Grain) M (Massive) CR (Crumb) GR (Granular) SBK (Subangular Block ABK (Angular Blocky) PL (Platy) PR (Prismatic)
II	SL (Sandy Loam) L (Loam)	0.8 - 0.6	0.4 - 0.3		
III	SI (Silt) SICL (Silty Clay Loam) CL (Clay Loam) SCL (Sandy Clay Loam) SLC (Silt Loam Clay)	0.6 - 0.3	0.3 - 0.15		
IV	SC (Sandy Clay) SIC (Silty Clay)	0.4 - 0.1	0.2 - 0.05		
	O (Organic)	None			

MOIST	WET
VFR (Very Friable)	NS (Non-sticky)
FR (Friable)	SS (Slightly Sticky)
FI (Firm)	S (Sticky)
VFI (Very Firm v. Very Sticky)	VS (Very Sticky)
EFI (Extremely Firm)	NP (Non-plastic)
	SP (Slightly Plastic)
	P (Plastic)
	VP (Very Plastic)

House 150' to Street

45' to LF SL

Lake

ON DEPTH In inches below natural soil surface
H OF FILL In inches from land surface
UCTIVE HORIZON Thickness and depth from land surface
OLITE S(suitable) or U(unsuitable)
ETNESS Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation
IFICATION S (Suitable), PS (Provisionally Suitable), or U (Unsuitable)

tion of saprolite shall be by pits.
rm Acceptance Rate (LTAR): gal/day/ft²

Show profile locations and other site features (dimensions, reference or benchmark, and North).

