DSCAPE POSITION	GROUP	SOIL TEXTURE	CONVENTIONAL 1955 LTAR	LPP 1997 LTAR	MINERALOGY/ CONSISTENCE	STRUCTURE
Concave Slope) Convex Slope) ainage Way) ebris Slump) ood Plain) ot Slope) ad Slope) ear Slope) se Slope) ige) uilder Slope) race)	I	S (Sand) LS (Loamy Sand)	1.2 - 0.8	1.6 - 0.4	NEC (Non-expansive) SEC (Slightly Expansive) EC (Expansive)	G (Single Grain) M (Massive) CR (Crumb) GR (Granular) SBK (Subangular Bloc ABK (Angular Blocky PL (Platy) PR (Prismatic)
	II	SL (Sandy Loam) L (Loam)	0.8 - 0.6	0.4 - 0.2		
	III	SI (Silt) SICL (Silty Clay Loam) CL (Clay Loam) SCL (Sandy Clay Loam) SLC (Silt Loam Clay)	0.6 - 0.2	0.2 - 0.15	MOIST	WET
	IV	SC (Sandy Clay) SIC (Silty Clay)	0.4 - 0.1	0.2 - 0.05	VFR (Very Friable) FR (Friable) FI (Firm) VFI (Very Firm / Very Sticky) EFI (Extremely Firm)	NS (Non-sticky) SS (Slightly Sticky) S (Sticky) VS (Very Sticky) NP (Non-plastic) SP (Slightly Plastic) P (Plastic) VP (Very Plastic)
		O (Organic)	None			

ON DEPTH Inches below natural soil surface
H OF FILL Inches from land surface
JCTIVE HORIZON Thickness and depth from land surface
PLATE S(suitable) or U(unsuitable)
VETNESS Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color and designation
IFICATION S (Suitable), PS (Provisionally Suitable), or U (Unsuitable)
tion of saprolite shall be by pits.
erm Acceptance Rate (LTAR): gal/day/ft²

Show profile locations and other site features (dimensions, reference or benchmark, and North).

