DEPARTMENT OF ENVIRONMENT, HEALTH, AND NATURAL RESOURCES
DIVISION OF ENVIRONMENTAL HEALTH
ON-SITE WASTEWATER SECTION

Sheet ___ of ___
PROPERTY ID #: ___
COUNTY: ___

03-P-01-04
4730777842

SOIL/SITE EVALUATION
for ON-SITE WASTEWATER SYSTEM

OWNER: Kenneth Millsaps
ADDRESS: 264 SPICEWOOD LOOP Traphill NC 28686
APPLICANT: SAME
APPLICATION DATE: 1-15-04
DATE EVALUATED: 2-21-04
PROPOSED FACILITY: 3 BR House
PROPOSED DESIGN FLOW (.1949): 360
PROPERTY SIZE: .43 AC
LOCATION OF SITE: SPICEWOOD LOT 52
PROPERTY RECORDED: ___
WATER SUPPLY: ☐ Private ☒ Public ☐ Well ☐ Spring ☐ Other ___
EVALUATION METHOD: ☒ Auger Boring ☐ Pit ☐ Cut
TYPE OF WASTEWATER: ☒ Sewage ☐ Industrial Process ☐ Mixed

PROFILE #	.1940 LANDSCAPE POSITION/ SLOPE %	HORIZON DEPTH (IN.)	SOIL MORPHOLOGY (.1941) STRUCTURE/ TEXTURE	SOIL MORPHOLOGY (.1941) CONSISTENCE/ MINERALOGY	OTHER PROFILE FACTORS .1942 SOIL WETNESS/ COLOR	.1943 SOIL DEPTH	.1956 SAPRO CLASS	.1944 RESTR HORIZ	PROFIL CLASS & LTAR
1	HOLE 1 6% L	0-6"	scl wk gr	fr ns sp mpo					
		6-48"	c mod abk	fi, s, sp, sep	chroma 2 @ 20"				OS
			L7 yellow/light red/some gray		H2O INFILTRATED IN HOLE				
2	HOLE 2 & HOLE 4 6% L	0-6"	scl wk gr	fr ns sp mpo					
		6-48"	c mod abk	fi s sp sep	chroma 2 @ 24"				US
			yellow/light red/some gray		HOLES 2 & 4				
					SHOT IN LPP NOT ENOUGH ROOM				US
3	HOLE 3 & HOLE 6 L L%	0-6"	scl wk gr	fr ns sp mpo					
		6-48"	c mod abk/sbk	fi s sp sep		>48"			PS .25
									PS .25
4	HOLE 5 & 7 L 6%	0-4"	scl wk gr	fr ns sp mpo					PS .3
		4-48"	c mod sbk	fi s sp sep		>48"			PS .3
			L7 sep. in ms. zones	< 50%					

DESCRIPTION	INITIAL SYSTEM	REPAIR SYSTEM
Available Space (.1945)	YES	YES
System Type(s)	Pump RR PANEL	LP PANEL
Site LTAR	.3	.25

OTHER FACTORS (.1946): ___
SITE CLASSIFICATION (.1948): PS
EVALUATED BY: L. LOOK
OTHER(S) PRESENT: K. MILLSAPS

LEGEND

use the following standard abbreviations

LANDSCAPE POSITION	GROUP	SOIL TEXTURE	CONVENTIONAL .1955 LTAR	LPP .1957 LTAR	MINERALOGY/ CONSISTENCE	STRUCTURE
CC (Concave Slope)	I	S (Sand)	1.2 - 0.8	0.6 - 0.4	NEXP (Non-expansive)	G (Single Grain)
CV (Convex Slope)		LS (Loamy Sand)			SEXP (Slightly Expansive)	M (Massive)
D (Drainage Way)					EXP (Expansive)	CR (Crumb)
DS (Debris Slump)	II	SL (Sandy Loam)	0.8 - 0.6	0.4 - 0.3		GR (Granular)
FP (Flood Plain)		L (Loam)				SBK (Subangular Blocky
FS (Foot Slope)						ABK (Angular Blocky)
H (Head Slope)	III	SI (Silt)	0.6 - 0.3	0.3 - 0.15		PL (Platy)
L (Linear Slope)		SICL (Silty Clay Loam)				PR (Prismatic)
N (Nose Slope)		CL (Clay Loam)				
R (Ridge)		SCL (Sandy Clay Loam)			MOIST	WET
S (Shoulder Slope)		SLC (Silt Loam Clay)				
T (Terrace)					VFR (Very Friable)	NS (Non-sticky)
	IV	SC (Sandy Clay)	0.4 - 0.1	0.2 - 0.05	FR (Friable)	SS (Slightly Sticky)
		SIC (Silty Clay)			FI (Firm)	S (Sticky)
					VFI (Very Firm v. Very Sticky)	VS (Very Sticky)
		O (Organic)	None		EFI (Extremely Firm)	NP (Non-plastic)
						SP (Slightly Plastic)
						P (Plastic)
						VP (Very Plastic)

NOTES

HORIZON DEPTH	In inches below natural soil surface
DEPTH OF FILL	In inches from land surface
RESTRICTIVE HORIZON	Thickness and depth from land surface
SAPROLITE	S(suitable) or U(unsuitable)
SOIL WETNESS	Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation
CLASSIFICATION	S (Suitable), PS (Provisionally Suitable), or U (Unsuitable)

Evaluation of saprolite shall be by pits.

Long-term Acceptance Rate (LTAR): gal/day/ft²

Show profile locations and other site features (dimensions, reference or benchmark, and North).

