-SITE ...ATER SECTION

for ON-SITE WASTEWATER SYSTEM

...ER: W BREWSTER APPLICANT: _____

...DRESS: _____ APPLICATION DATE: _____ DATE EVALUATED: _____

...OPOSED FACILITY: _____ PROPOSED DESIGN FLOW (.1949): _____ PROPERTY SIZE: _____

...CATION OF SITE: MARTHAS VINEYARD LOT 1 PROPERTY RECORDED: _____

...TER SUPPLY: ☐ Private ☐ Public ☐ Well ☐ Spring ☐ Other _____

...ALUATION METHOD: ☐ Auger Boring ☐ Pit ☐ Cut

...PE OF WASTEWATER: ☐ Sewage ☐ Industrial Process ☐ Mixed

.1940 LAND-SCAPE POSITION/ SLOPE %	HORI-ZON DEPTH (IN.)	SOIL MORPHOLOGY (.1941) .1941 STRUCTURE/ TEXTURE	.1941 CONSISTENCE/ MINERALOGY	OTHER PROFILE FACTORS .1942 SOIL WETNESS/ COLOR	.1943 SOIL DEPTH	.1956 SAPRO CLASS	.1944 RESTR HORIZ	PROFILE CLASS & LTAR
	0-6	SCL GR	FRI SSSP					PS
	6-26	LS MFSBK	FI SP					
	26-43	YLCL MSBK	FRI SSSP	Few SAP				.3
	0-4	SCL GR	FRI SSSP					
	4-26	LS MFSBK	FRI SP					PS
	26-50	YRCL MFSBK	FRI SSSP	Few SAP				.3

...ABLE SOILS (.1943)

...EM TYPE(S)

EVALUATED BY: _____

DSCAPE POSITION	GROUP	SOIL TEXTURE	CONVENTIONAL 1955 LTAR	LPP 1957 LTAR	MINERALOGY/ CONSISTENCE	STRUCTURE
Concave Slope)	I	S (Sand)	1.2 - 0.8	0.6 - 0.4	NEXP (Non-expansive)	G (Single Grain)
Convex Slope)		LS (Loamy Sand)			SEXP (Slightly Expansive)	M (Massive)
ainage Way)					EXP (Expansive)	CR (Crumb)
ebris Slump)	II	SL (Sandy Loam)	0.8 - 0.6	0.4 - 0.3		GR (Granular)
ood Plain)		L (Loam)				SBK (Subangular Block
ot Slope)						ABK (Angular Blocky)
ad Slope)	III	SI (Silt)	0.6 - 0.3	0.3 - 0.15		PL (Platy)
ear Slope)		SICL (Silty Clay Loam)				PR (Prismatic)
se Slope)		CL (Clay Loam)				
ge)		SCL (Sandy Clay Loam)			MOIST	WET
ulder Slope)		SLC (Silt Loam Clay)				
ace)					VFR (Very Friable)	NS (Non-sticky)
	IV	SC (Sandy Clay)	0.4 - 0.1	0.2 - 0.05	FR (Friable)	SS (Slightly Sticky)
		SIC (Silty Clay)			FI (Firm)	S (Sticky)
					VFI (Very Firm v. Very Sticky)	VS (Very Sticky)
		O (Organic)	None		EFI (Extremely Firm)	NP (Non-plastic)
						SP (Slightly Plastic)
						P (Plastic)
						VP (Very Plastic)

ON DEPTH	In inches below natural soil surface
I OF FILL	In inches from land surface
CTIVE HORIZON	Thickness and depth from land surface
LITE	S(suitable) or U(unsuitable)
'ETNESS	Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation
'FICATION	S (Suitable), PS (Provisionally Suitable), or U (Unsuitable)

ion of saprolite shall be by pits.

rm Acceptance Rate (LTAR): gal/day/ft²

Show profile locations and other site features (dimensions, reference or benchmark, and North).

