...SITE WASTEWATER SECTION

PROP. ID #:
COUNTY:

for ON-SITE WASTEWATER SYSTEM

...ER: W. BREWSTER APPLICANT:

...DRESS: APPLICATION DATE: DATE EVALUATED:

...OPOSED FACILITY: PROPOSED DESIGN FLOW (.1949): PROPERTY SIZE:

...CATION OF SITE: MARTHAS VINEYARD LOT 36 PROPERTY RECORDED:

...TER SUPPLY: ☐ Private ☐ Public ☐ Well ☐ Spring ☐ Other

...ALUATION METHOD: ☐ Auger Boring ☐ Pit ☐ Cut

...PE OF WASTEWATER: ☐ Sewage ☐ Industrial Process ☐ Mixed

.1940 LAND-SCAPE POSITION/ SLOPE %	HORI-ZON DEPTH (IN.)	SOIL MORPHOLOGY (.1941) .1941 STRUCTURE/ TEXTURE	SOIL MORPHOLOGY (.1941) .1941 CONSISTENCE/ MINERALOGY	OTHER PROFILE FACTORS .1942 SOIL WETNESS/ COLOR	OTHER PROFILE FACTORS .1943 SOIL DEPTH	OTHER PROFILE FACTORS .1956 SAPRO CLASS	OTHER PROFILE FACTORS .1944 RESTR HORIZ	PROFILE CLASS & LTAR
	0-20	BSCL SN4	FI/FRI SSAP					PS
	20-34	RCSCL SN4/MH FI/FRI		-Fe-				
	34-40	YRCL SN4	FRI SSAP					.3
	0-16	DSCL SN4	FI/FRI SSAP					PS
	16-36	RCSCL SN4/MH FI/FRI	SSAP					
	36-50	YRCL SN4	FRI SSAP					.3

...ilable Space (...

...em Type(s)

DSCAPE POSITION	GROUP	SOIL TEXTURE	CONVENTIONAL 1955 LTAR	CPP 1957 LTAR	MINERALOGY/ CONSISTENCE	STRUCTURE
Concave Slope)	I	S (Sand)	1.2 - 0.8	0.6 - 0.4	NEXP (Non-expansive)	G (Single Grain)
Convex Slope)		LS (Loamy Sand)			SEXP (Slightly Expansive)	M (Massive)
ainage Way)					EXP (Expansive)	CR (Crumb)
ebris Slump)	II	SL (Sandy Loam)	0.8 - 0.6	0.4 - 0.3		GR (Granular)
ood Plain)		L (Loam)				SBK (Subangular Block
ot Slope)						ABK (Angular Blocky)
ad Slope)	III	SI (Silt)	0.6 - 0.3	0.3 - 0.15		PL (Platy)
ear Slope)		SICL (Silty Clay Loam)				PR (Prismatic)
ce Slope)		CL (Clay Loam)				
gs)		SCL (Sandy Clay Loam)			MOIST	WET
ulder Slope)		SLC (Silt Loam Clay)				
ace)					VFR (Very Friable)	NS (Non-sticky)
	IV	SC (Sandy Clay)	0.4 - 0.1	0.2 - 0.05	FR (Friable)	SS (Slightly Sticky)
		SIC (Silty Clay)			FI (Firm)	S (Sticky)
					VFI (Very Firm v. Very Sticky)	VS (Very Sticky)
		O (Organic)	None		EFI (Extremely Firm)	NP (Non-plastic)
						SP (Slightly Plastic)
						P (Plastic)
						VP (Very Plastic)

ON DEPTH In inches below natural soil surface
I OF FILL In inches from land surface
ICTIVE HORIZON Thickness and depth from land surface
LITE S(suitable) or U(unsuitable)
'ETNESS Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation
'FICATION S (Suitable), PS (Provisionally Suitable), or U (Unsuitable)

ion of saprolite shall be by pits.
rm Acceptance Rate (LTAR): gal/day/ft²

Show profile locations and other site features (dimensions, reference or benchmark, and North).