...ISION OF ENVIRONMENTAL HEALTH
...-SITE WASTEWATER SECTION

PROPERTY ID #: _____
COUNTY: _____

SOIL/SITE EVALUATION
for ON-SITE WASTEWATER SYSTEM

...ER: Brewster APPLICANT: _____
...DRESS: _____ APPLICATION DATE: _____ DATE EVALUATED: _____
...OPOSED FACILITY: _____ PROPOSED DESIGN FLOW (.1949): _____ PROPERTY SIZE: _____
...CATION OF SITE: Lot 15 Marthas Vineyard PROPERTY RECORDED: _____
...TER SUPPLY: ☐ Private ☐ Public ☐ Well ☐ Spring ☐ Other _____
...ALUATION METHOD: ☐ Auger Boring ☐ Pit ☐ Cut
...PE OF WASTEWATER: ☐ Sewage ☐ Industrial Process ☐ Mixed

.1940 LANDSCAPE POSITION/ SLOPE %	HORIZON DEPTH (IN.)	SOIL MORPHOLOGY (.1941) .1941 STRUCTURE/ TEXTURE	.1941 CONSISTENCE/ MINERALOGY	OTHER PROFILE FACTORS .1942 SOIL WETNESS/ COLOR	.1943 SOIL DEPTH	.1956 SAPRO CLASS	.1944 RESTR HORIZ	PROFILE CLASS & LTAR
	0-10							PS
	10-56			Few Stn	45"+			.25
	0-6							
	6-29							S
26-1	29-45			Few Stn				3

	...EM	REPAIR SYSTEM
...em Type(s)		
LTAR		

OTHER FACTORS (.1946): _____
SITE CLASSIFICATION (.1948): _____
EVALUATED BY: _____
OTHER(S) PRESENT: _____

use the following standard abbreviations.

DSCAPE POSITION	GROUP	SOIL TEXTURE	CONVENTIONAL 1955 LTAR	LPP 1957 LTAR	MINERALOGY/ CONSISTENCE	STRUCTURE
Concave Slope)	I	S (Sand)	1.2 - 0.8	0.6 - 0.4	NEXP (Non-expansive)	G (Single Grain)
Convex Slope)		LS (Loamy Sand)			SEXP (Slightly Expansive)	M (Massive)
ainage Way)					EXP (Expansive)	CR (Crumb)
ebris Slump)	II	SL (Sandy Loam)	0.8 - 0.6	0.4 - 0.3		GR (Granular)
ood Plain)		L (Loam)				SBK (Subangular Blocky)
ot Slope)						ABK (Angular Blocky)
ad Slope)	III	SI (Silt)	0.6 - 0.3	0.3 - 0.15		PL (Platy)
ear Slope)		SICL (Silty Clay Loam)				PR (Prismatic)
se Slope)		CL (Clay Loam)				
ge)		SCL (Sandy Clay Loam)			MOIST	WET
ulder Slope)		SLC (Silt Loam Clay)				
race)					VFR (Very Friable)	NS (Non-sticky)
	IV	SC (Sandy Clay)	0.4 - 0.1	0.2 - 0.05	FR (Friable)	SS (Slightly Sticky)
		SIC (Silty Clay)			FI (Firm)	S (Sticky)
					VFI (Very Firm v. Very Sticky)	VS (Very Sticky)
		O (Organic)	None		EFI (Extremely Firm)	NP (Non-plastic)
						SP (Slightly Plastic)
						P (Plastic)
						VP (Very Plastic)

ON DEPTH	In inches below natural soil surface
OF FILL	In inches from land surface
CTIVE HORIZON	Thickness and depth from land surface
LITE	S(suitable) or U(unsuitable)
ETNESS	Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation
IFICATION	S (Suitable), PS (Provisionally Suitable), or U (Unsuitable)

ion of saprolite shall be by pits.

rm Acceptance Rate (LTAR): gal/day/ft²

Show profile locations and other site features (dimensions, reference or benchmark, and North).

