LEGEND

use the following standard abbreviations

LANDSCAPE POSITION

- CC (Concave Slope)
- CV (Convex Slope)
- D (Drainage Way)
- DS (Debris Slump)
- FP (Flood Plain)
- FS (Foot Slope)
- H (Head Slope)
- L (Linear Slope)
- N (Nose Slope)
- R (Ridge)
- S (Shoulder Slope)
- T (Terrace)

GROUP	SOIL TEXTURE	CONVENTIONAL .1955 LTAR	LPP .1957 LTAR
I	S (Sand) LS (Loamy Sand)	1.2 - 0.8	0.6 - 0.4
II	SL (Sandy Loam) L (Loam)	0.8 - 0.6	0.4 - 0.3
III	SI (Silt) SICL (Silty Clay Loam) CL (Clay Loam) SCL (Sandy Clay Loam) SLC (Silt Loam Clay)	0.6 - 0.3	0.3 - 0.15
IV	SC (Sandy Clay) SIC (Silty Clay)	0.4 - 0.1	0.2 - 0.05
	O (Organic)	None	

MINERALOGY/ CONSISTENCE

- NEXP (Non-expansive)
- SEXP (Slightly Expansive)
- EXP (Expansive)

MOIST

- VFR (Very Friable)
- FR (Friable)
- FI (Firm)
- VFI (Very Firm v. Very Sticky)
- EFI (Extremely Firm)

STRUCTURE

- G (Single Grain)
- M (Massive)
- CR (Crumb)
- GR (Granular)
- SBK (Subangular Blocky)
- ABK (Angular Blocky)
- PL (Platy)
- PR (Prismatic)

WET

- NS (Non-sticky)
- SS (Slightly Sticky)
- S (Sticky)
- VS (Very Sticky)
- NP (Non-plastic)
- SP (Slightly Plastic)
- P (Plastic)
- VP (Very Plastic)

NOTES

HORIZON DEPTH	In inches below natural soil surface
DEPTH OF FILL	In inches from land surface
RESTRICTIVE HORIZON	Thickness and depth from land surface
SAPROLITE	S(suitable) or U(unsuitable)
SOIL WETNESS	Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation
CLASSIFICATION	S (Suitable), PS (Provisionally Suitable), or U (Unsuitable)

Evaluation of saprolite shall be by pits.

Long-term Acceptance Rate (LTAR): gal/day/ft²

Show profile locations and other site features (dimensions, reference or benchmark, and North).

