LEGEND

use the following standard abbreviations.

LANDSCAPE POSITION	GROUP	SOIL TEXTURE	CONVENTIONAL 1955 LTAR	LPP 1957 LTAR	MINERALOGY CONSISTENCE	STRUCTURE
CC (Concave Slope)	I	S (Sand)	1.2 - 0.8	0.6 - 0.4	NEXP (Non-expansive)	G (Single Grain)
CV (Convex Slope)		LS (Loamy Sand)			SEXP (Slightly Expansive)	M (Massive)
D (Drainage Way)					EXP (Expansive)	CR (Crumb)
DS (Debris Slump)	II	SL (Sandy Loam)	0.8 - 0.6	0.4 - 0.3		GR (Granular)
FP (Flood Plain)		L (Loam)				SBK (Subangular Blo
FS (Foot Slope)						ABK (Angular Blocky
HS (Head Slope)	III	SI (Silt)	0.6 - 0.3	0.3 - 0.15		PL (Platy)
LS (Linear Slope)		SICL (Silty Clay Loam)				PR (Prismatic)
NS (Nose Slope)		CL (Clay Loam)				
R (Ridge)		SCL (Sandy Clay Loam)				
SS (Shoulder Slope)		SLC (Silt Loam Clay)			MOIST	WET
T (Terrace)	IV	SC (Sandy Clay)	0.4 - 0.1	0.2 - 0.05	VFR (Very Friable)	NS (Non-sticky)
		SIC (Silty Clay)			FR (Friable)	SS (Slightly Sticky)
					FI (Firm)	S (Sticky)
		O (Organic)	None		VFI (Very Firm v. Very Sticky)	VS (Very Sticky)
					EFI (Extremely Firm)	NP (Non-plastic)
						SP (Slightly Plastic)
						P (Plastic)
						VP (Very Plastic)

TES
ORIZON DEPTH In inches below natural soil surface
EPTH OF FILL In inches from land surface
STRICTIVE HORIZON Thickness and depth from land surface
PROLITE S(suitable) or U(unsuitable)
IL WETNESS Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designatic
ASSIFICATION S (Suitable), PS (Provisionally Suitable), or U (Unsuitable)

lusion of saprolite shall be by pits.

g-term Acceptance Rate (LTAR): gal/day/ft²

Show profile locations and other site features (dimensions, reference or benchmark, and North).

