DENR/DEH

ON-SITE WASTEWATER SECTION

Sheet 1 of 1
PROPERTY ID #: 4891-42-7172
COUNTY: Jackson

SOIL/SITE EVALUATION
for ON-SITE WASTEWATER SYSTEM

OWNER: Richard Shaw
ADDRESS: 162 Rock Springs Rd Dillsboro
PROPOSED FACILITY: 3 bd. Home
LOCATION OF SITE: 901 Tum Shuffle Rd
APPLICATION DATE 2/7/11
DATE EVALUATED: 4 March 11
PROPERTY SIZE: 12 ac.
PROPERTY RECORDED:
PROPOSED DESIGN FLOW (.1949): 360 g/d
WATER SUPPLY: • Private • (Public) • Well • Spring • Other
EVALUATION METHOD: • Auger Boring • (Pit) • Cut
TYPE OF WASTEWATER: • (Sewage) • Industrial Process • Mixed

PROFILE #	.1940 LANDSCAPE POSITION/ SLOPE %	HORIZON DEPTH (IN.)	SOIL MORPHOLOGY (.1941) .1941 STRUCTURE/ TEXTURE	SOIL MORPHOLOGY (.1941) .1941 CONSISTENCE/ MINERALOGY	OTHER PROFILE FACTORS .1942 SOIL WETNESS/ COLOR	.1943 SOIL DEPTH	.1956 SAPRO CLASS	.1944 RESTR HORIZ	PROFILE CLASS & LTAR
1	L 6%	0-10	gr SL	vfr / soft	760	36	SL PS	NA	PS 0.3
		10-16	SBK / CL	fr / sl sticky					
		16-30	SBK / C	fi / sl sticky					
		30-36	SBK / CL	fr / sl sticky					
		36-60+	SAP						
2	L 6%	0-8	gr / SL	vfr / soft	760	32	SL PS	NA	PS 0.3
		8-15	SBK / CL	fr / sl sticky					
		15-32	SBK / C	fi / sl sticky					
		32-60+	SAP						
3	N 9%	0-6	gr / SL	vfr / soft	760	34	SL PS	NA	PS 0.3
		6-12	SBK / CL	fr / sl sticky					
		12-28	SBK / C	fi / sl sticky					
		28-34	SBK / CL	fr / sl sticky					
		34-60+	SAP						
4	N 8%	6-8	gr / SL	vfr / soft	760	36	SL PS	NA	PS 0.3
		8-16	SBK / CL	fr / sl sticky					
		16-30	SBK / C	fi / sl sticky					
		30-36	SBK / CL	fr / sl sticky					
		36-60	SAP						

DESCRIPTION	INITIAL SYSTEM	REPAIR SYSTEM
Available Space (.1945)	PS	PS
System Type(s)	III	III
Site LTAR	0.3	0.3

OTHER FACTORS (.1946): PS
SITE CLASSIFICATION (.1948): PS
EVALUATED BY: TCH
OTHER(S) PRESENT:

COMMENTS:

LEGEND

use the following standard abbreviations

LANDSCAPE POSITION	GROUP	SOIL TEXTURE	CONVENTIONAL .1955 LTAR*	LPP .1957 LTAR*	MINERALOGY/ CONSISTENCE	STRUCTURE
CC (Concave Slope)	I	S (Sand)	1.2 - 0.8	0.6 - 0.4	NEXP (Non-expansive)	G (Single Grain)
CV (Convex Slope)		LS (Loamy Sand)			SEXP (Slightly Expansive)	M (Massive)
D (Drainage Way)					EXP (Expansive)	CR (Crumb)
DS (Debris Slump)	II	SL (Sandy Loam)	0.8 - 0.6	0.4 - 0.3		GR (Granular)
FP (Flood Plain)		L (Loam)				SBK (Subangular Blocky)
FS (Foot Slope)						ABK (Angular Blocky)
H (Head Slope)	III	Si (Silt)	0.6 - 0.3	0.3 - 0.15		PL (Platy)
L (Linear Slope)		SiCL (Silty Clay Loam)				PR (Prismatic)
N (Nose Slope)		CL (Clay Loam)				
R (Ridge)		SCL (Sandy Clay Loam)			**MOIST**	**WET**
S (Shoulder Slope)		SiL (Silt Loam)				
T (Terrace)					VFR (Very Friable)	NS (Non-sticky)
	IV	SC (Sandy Clay)	0.4 - 0.1	0.2 - 0.05	FR (Friable)	SS (Slightly Sticky)
		SiC (Silty Clay)			FI (Firm)	S (Sticky)
		C (Clay)			VFI (Very Firm v. Very Sticky)	VS (Very Sticky)
		O (Organic)	None	None	EFI (Extremely Firm)	NP (Non-plastic)
						SP (Slightly Plastic)
						P (Plastic)
						VP (Very Plastic)

*Adjust LTAR due to depth, consistence, structure, soil wetness, landscape, position, wastewater flow and quality.


NOTES

HORIZON DEPTH	In inches below natural soil surface
DEPTH OF FILL	In inches from land surface
RESTRICTIVE HORIZON	Thickness and depth from land surface
SAPROLITE	S(suitable) or U(unsuitable)
SOIL WETNESS	Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation
CLASSIFICATION	S (Suitable), PS (Provisionally Suitable), or U (Unsuitable)

Evaluation of saprolite shall be by pits.

Long-term Acceptance Rate (LTAR): gal/day/ft^2

Show profile locations and other site features (dimensions, reference or benchmark, and North).



DENR (######)
Review (#####)

Rock Springs Rd.